



400 Series II Stationary Single Screw Vertical Mixer Specifications

The name customers have entrusted for material handling solutions since 1948!

| | U/M | 140 | 200 |
|---|-----------------------------------|---|----------------|
| CAPACITY | | | |
| Mixing | ft ³ (m ³) | 140 (3.9) | 200 (5.7) |
| w/Optional Extension | ft ³ (m ³) | 180 (5.0) | 240 (6.8) |
| UNIT | | | |
| Empty Wt. | lb (kg) | 4,184 (1,898) | 4,575 (2,075) |
| Max. Load @ 25lb./cu.ft. | lb (kg) | 3,500 (1,588) | 5,000 (2,268) |
| Max. Load @ 25lb./cu.ft. w/9 in. Ext. | lb (kg) | 4,500 (2,045) | 6,000 (2,722) |
| Max. Gross Wt. | lb (kg) | 8,684 (3,943) | 10,575 (4,797) |
| No. of Screws (See Options below) | | 1 | 1 |
| Overall Length | in (m) | 118 1/2 (3.0) | 118 1/2 (3.0) |
| Overall Height | in (m) | 86 5/8 (2.2) | 100 1/8 (2.5) |
| Overall Height w/9 in. Ext. | in (m) | 95 5/8 (2.4) | 109 1/8 (2.8) |
| Overall Width | in (m) | 88 1/2 (2.2) | 88 1/2 (2.2) |
| Screw Flighting Thickness | in (mm) | 1/2 (13) | 1/2 (13) |
| Floor Thickness | in (mm) | 1/2 (13) | 1/2 (13) |
| Sidewall Thickness | in (mm) | 1/4 (6) | 1/4 (6) |
| Horsepower Requirements | | (1) 10 HP or (2) 7½ or (2) 10 HP or (1) 15 HP or (1) 20 HP (1) 25 HP or (1) 30 HP | |
| Hour Meter | | Std. | Std. |
| Scale System | | 3-Point | 3-Point |
| DOOR OPENINGS | | | |
| Height | in (mm) | 31 (787) | 31 (787) |
| Width | in (mm) | 24 (610) | 24 (610) |
| Location | | R.H., L.H., or Both | |
| OPTIONS | | | |
| Tru Taper™ Vertical Mixer Screw Cone Top with Dual Kicker (not included in basic unit) | | Choose One Size Screw for Your Mixing Needs | |
| Maximum No. of Knives+ | | 4 | 5 |
| Manual or Electric Door Control | | R.H. or L.H. | R.H. or L.H. |
| Discharge Chute with or without Magnet | | Opt. | Opt. |
| Tub Mounted Magnet‡ | | Opt. | Opt. |
| Wide Selection of Indicators | | dinamica generale®, Weigh-Tronix®, & Digi-Star® | |
| Ladder | | Opt. | Opt. |
| Restrictors | | 2 | 2 |
| Variable Frequency Drive Pkg. (VFD) | | Opt. | Opt. |

‡ Quantity varies with material in ration and processing time.

+ Patent Pending.

Options include:

DIG IN with the RAPTOR™*!



Engineered to complement our standard knives, this AR knife features a forward-facing design to dig in, hook, and cut bales faster and more aggressively!

2 Sizes Available!



PROTECT WHAT MATTERS with a Tub Mounted Magnet*!

Exclusive to Patz!

Encased in stainless steel, this exclusive magnet is mounted into the Patz Vertical Mixer tub wall on a hinged assembly for effective removal of tramp metal from rations.

*Patent Pending

Actual tramp metal removed from magnet.

This mixer is designed to handle a variety of feedstuffs based on an estimated 25 lbs. per cubic foot. Do not exceed stated maximum load. Contact Patz for applications requiring heavier materials. Specifications and prices subject to change without notice.

Proven Performance you can count on!



CAUTION: Never operate Patz equipment without all shields and guards in place. **Safety Is No Accident.** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.

Watch online



mixer video!