



# 1200 Series Trailer Single Screw Vertical Mixer Specifications



The name farmers have entrusted for feeding solutions since 1948!

	U/M	420		500		615		
<b>CAPACITY</b>								
Mixing	ft <sup>3</sup> (m <sup>3</sup> )	420 (11.8)		500 (14.2)		615 (17.4)		
w/extension	ft <sup>3</sup> (m <sup>3</sup> )	490 (13.9)		575 (16.3)		690 (19.5)		
<b>UNIT</b>								
Empty Wt.	lb (kg)	9,500 (4,309)		9,980 (4,527)		10,475 (4,751)		
Max. Load @ 25#/cu. ft.	lb (kg)	10,500 (4,763)		12,500 (5,670)		15,375 (6,974)		
Max. Gross Wt.	lb (kg)	20,000 (9,072)		22,480 (10,197)		25,850 (11,725)		
No. of Screws (see options below)		1		1		1		
Overall Length	in (m)	220 (5.6)		223-3/4 (5.7)		228 (5.8)		
Overall Height	in (m)	97 (2.5)		106 (2.7)		119 (3)		
Overall Width	in (m)	109 (2.8)		109 (2.8)		109 (2.8)		
Screw Flighting Thickness	in (mm)	5/8 (16)		5/8 (16)		5/8 (16)		
Floor Thickness	in (mm)	3/4 (19)		3/4 (19)		3/4 (19)		
Sidewall Thickness	in (mm)	1/4 (6)		1/4 (6)		1/4 (6)		
Minimum PTO Horsepower*		85		90		110		
Viewing Platform		Access From Right and Left Sides						
Hour Meter		Std.		Std.		Std.		
Scale System		4-Point		4-Point		4-Point		
No. of Tires		4		4		4		
Tire Size		245 70R 19.5 Tubeless Truck Tire						
Operating Speed (RPM)		540 or 1000		1000		1000		
<b>DOOR OPENINGS</b>								
Height	in (mm)	Front/Rear	Side	Front/Rear	Side	Front/Rear	Side	
Width	in (mm)	26 (660)	39 (991)	30 (762)	39 (991)	30 (762)	39 (991)	
		42 (1,067)	34 (864)	42 (1,067)	34 (864)	42 (1,067)	34 (864)	
Discharge		Various discharge packages available. See Dealer for details.						
Ground Clearance		Varies with discharge selected.						
<b>OPTIONS</b>								
‡Vortex® Vertical Mixer Screw (not included in basic unit)		Choose One Type of Screw for Your Mixing Needs.						
Single or Dual Kicker								
Maximum No. of Knives+		7		9		9		
2-Speed Drive Pkg.		Opt.		Opt.		Opt.		
Rubber Side Extensions		Opt.		Opt.		Opt.		
Hay Retainer		Opt.		Opt.		Opt.		
Discharge Chute w/ or w/out Magnet		Opt.		Opt.		Opt.		
Discharge Conveyor(s)		Various Opt.						
Tub Mounted Magnet‡		Opt.		Opt.		Opt.		
Rear Commodity Door		Opt.		Opt.		Opt.		
Indicator Extension Arm		Opt.		Opt.		Opt.		
Wide Selection of Indicators		dinamica generale®, Weigh-Tronix®, or Digi-Star®						
Camera Package		Opt.		Opt.		Opt.		
Battery Mount		Opt.		Opt.		Opt.		
Ladder		Opt.		Opt.		Opt.		

\* Minimum PTO horsepower requirement is for continuous run. Starting the mixer under load will require higher PTO horsepower.

‡ Patent Pending.

+ Quantity varies with material in the ration and processing time.



**CAUTION:** Never operate Patz equipment without all shields and guards in place. **Safety Is No Accident.** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.

