Additional **Patz** Conveyors

Full line of Distribution Conveyors with belt widths of 12, 16, 24, and 36 inches.

Move material exactly where you want it with one-way or two-way conveying, adjustable elbow or straight-line conveying and plowoff. Open pan design reduces belt friction for lower power requirements.



STAND	RD Equipment	8912	8916	1608
Load Capacity	Up to 56 ft ³ /min (1.6 m ³ /min), 3,700 lbs/min (1,678 kg/min).			
	Up to 90 ft ³ /min (2.6 m ³ /min), 3,700 lbs/min (1,678 kg/min).			
	Up to 95 ft ³ /min (2.7 m ³ /min), 3,900 lbs/min (1,769 kg/min).			
Overall Lengths	10' (3.0) to 120' (36.6 m) in 10' (3.0 m) increments.			
	10' (3.0) to 160' (48.8 m) in 10' (3.0 m) increments.			
	10' (3.0) to 200' (61 m) in 10' (3.0 m) increments.			
	Maximum length of individual bed section is 10' (3.0 m); modular sections bolt together for lengths beyond 10' (3.0 m).			
Span	Up to 20' (6.1 m) between supports.			
Belt Width	12″ (305 mm).			
	16" (406 mm).			
Belt Speed	370 ft/min (112.8 m/min), 260 ft/min (79.2 m/min), 130 ft/min (39.6 m/min) or 65 ft/min (19.8 m/min) (depends on drive selected)			
	390 ft/min (118.9 m/min), 260 ft/ min (79.2 m/min) (depends on drive selected)			
Drive Pulley	5" (127 mm) dia., crowned, steel, rubber lagged.			
	8" (203 mm) dia., crowned, steel, rubber lagged.			
Tail Pulley	5" (127 mm) dia., finned, steel.	•	•	
OPTION	AL Equipment	8912	8916	1608
Incline	Up to 15° with smooth belt (limit to 5° with frozen material).			
	Up to 30° with textured belt.			
Drive Motors	1 to 3 HP, 1 Ph. or 3 Ph. electric motor drive; hydraulic motor drive also available.	-	•	
	3 HP or 5 HP, 1 Ph. or 3 Ph. electric motor drive.			•

Proven Performance You Can Count On! Patz Corporation

917 Business 141, POB 7 • Pound, Wisconsin 54161-0007 Ph: (920) 897-2251 • Fax: (920) 897-2142 www.patzcorp.com • info@patzcorp.com

PA-26124 Rev. 1/14 ©2012-2014 Patz Corporation Printed in U.S.A.





