

2400 Series II Twin Screw Vertical Mixer Specifications



2400 Series II Vortex®	U/M	650
Mixing Capacity w/ Extensions (9.25 in)	ft ³ /m ³	755 (21)
Weight	lbs (kg)	16,500 (7,484)
XH Empty Weight	lbs (kg)	18,000 (8,165)
Max Load @ 25 lb/ft ³	lbs (kg)	16,250 (7,371)
Max Gross Weight	lbs (kg)	32,750 (14,855)
Floor Thickness	in (mm)	3/4 (19)
Sidewall Thickness	in (mm)	1/4 (6); XH 3/8 (9)
Door Opening Height x Width (Rear)	in (mm)	26 (660) x 42 (1,067)
Door Opening Height x Width (Side - 2 Locations)	in (mm)	39 (991) x 34 (864)
Viewing Platform		Front w/ Right/Left Access
Screw Flighting Thickness	in (mm)	5/8 (16); XH 3/4 (19)
Screw Height x Diameter	in (mm)	44 (1,118)/ 54 (1,372) x 96 (2,438)
Knife Positions Per Screw		7
Operating Speed	RPM	1,000
Drive Package		Direct/2-Speed Manual; 2-Speed Powershift, 20/21 - Spline
Minimum PTO HP (Continuous Run)	HP	80
Trailer Type		Split Dual
Scale System		4-Point
Tires		(4) 285/70 R 19.5 Tubeless Implement Truck Tires
OPTIONS		
Screw Knives - Raptor - Serrated Rubber Side Extensions	Hay Retainer Discharge Chute w/ or w/o Magnet Discharge Conveyor Tub Mounted Magnet	Selection of Indicators - Digi-Star® - dinamica generale® - Weigh-Tronix®
		Camera Package Ladder (Rear Location) Planetary Cooling System Hydraulic Control Center

2400 Series II Vortex®	U/M	750
Mixing Capacity w/ Extensions (9.25 in)	ft ³ /m ³	860 (24)
Weight	lbs (kg)	17,500 (7,938)
XH Empty Weight	lbs (kg)	19,400 (8,800)
Max Load @ 25 lb/ft ³	lbs (kg)	18,750 (8,505)
Max Gross Weight	lbs (kg)	36,250 (16,443)
Floor Thickness	in (mm)	3/4 (19)
Sidewall Thickness	in (mm)	1/4 (6); XH 3/8 (9)
Door Opening Height x Width (Rear)	in (mm)	30 (762) x 42 (1,067)
Door Opening Height x Width (Side - 2 Locations)	in (mm)	39 (991) x 34 (864)
Viewing Platform		Front w/ Right/Left Access
Screw Flighting Thickness	in (mm)	5/8 (16); XH 3/4 (19)
Screw Height x Diameter	in (mm)	44 (1,118)/ 54 (1,372) x 96 (2,438)
Knife Positions Per Screw		7
Operating Speed	RPM	1,000
Drive Package		Direct/2-Speed Manual; 2-Speed Powershift, 20/21 - Spline
Minimum PTO HP (Continuous Run)	HP	80
Trailer Type		Split Dual
Scale System		4-Point
Tires		(4) 285/70 R 19.5 Tubeless Implement Truck Tires
OPTIONS		
Screw Knives - Raptor - Serrated Rubber Side Extensions	Hay Retainer Discharge Chute w/ or w/o Magnet Discharge Conveyor Tub Mounted Magnet	Selection of Indicators - Digi-Star® - dinamica generale® - Weigh-Tronix®
		Camera Package Ladder (Rear Location) Planetary Cooling System Hydraulic Control Center