


2400 Series II Truck Mount Twin Screw Vertical Mixer

Specifications



2400 Series II  Vortex®	U/M	810	950	1100
Mixing Capacity w/ Extensions (9.25 in)	ft³/m³	950 (26.9)	1100 (31.1)	1270 (36)
Empty Weight	lbs (kg)	17,200 (7,802)	18,470 (8,378)	19,170 (8,695)
XH Empty Weight	lbs (kg)	19,000 (8,618)	20,900 (9,480)	22,000 (9,979)
Max Load @ 25 lb./ft.³	lbs (kg)	20,250 (9,185)	23,750 (10,773)	27,500 (12,473)
Max Gross Weight	lbs (kg)	37,700 (17,100)	40,800 (18,507)	46,670 (21,169)
Floor Thickness	in (mm)	3/4 (19)		
Sidewall Thickness	in (mm)	1/4 (6); XH 3/8 (9)		
Door Opening Height x Width (Front - Back)	in (mm)	26 (660) x 42 (1,067)	30 (762) x 42 (1,067)	
Door Opening Height x Width (Side - 4 Locations)	in (mm)	39 (991) x 34 (864)		
Viewing Platform		Front; Right/Left Access		
Screw Flighting Thickness	in (mm)	5/8 (16); XH 3/4 (19)		
Screw Height x Diameter	in (mm)	44 (1,118) x 108 (2,743)	54 (1,372) x 108 (2,743)	54 (1,372) x 108 (2,743)
Knife Positions Per Screw		5	7	11
Operating Speed	RPM	1,000 (Planetary) or 2,000 (Direct Hydraulic Drive)		
Drive Package		Low Profile Planetary or Direct Hydraulic Drive		
Scale System		4-Point		

OPTIONS

Vertical Mixer Screw
 - Multi-Angle
 - Knives
 Side Extensions
 - Rubber/Steel

Hay Retainer
 Discharge Chute w/ or w/o Magnet
 Discharge Conveyor
 Tub Mounted Magnet

Selection of Indicators
 - Digi-Star®,
 - dinamica generale®
 - Weigh-Tronix®

Camera Package
 Ladder (Rear Location)
 Planetary Cooling System
 Hydraulic Control Center



CAUTION: Never operate Patz equipment without all shields and guards in place. **Safety Is No Accident.** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.