

# 400 SERIES II STATIONARY SINGLE SCREW VERTICAL MIXERS



**FEEDINGSOLUTIONS**  
www.patzcorp.com

**FEEDING IS BELIEVING!**  
Schedule a DEMO Today!


**INVESTMENT FLEXIBILITY**  
Ask Dealer for Financing Details



# 400 Series II Stationary Single Screw Vertical Mixer

## Specifications



400 Series II  Tru Taper™	U/M	140	200
Mixing Capacity w/ Extensions (9 in)	ft <sup>3</sup> /m <sup>3</sup>	180 (5)	240 (6.8)
Empty Weight	lbs (kg)	4,184 (1,898)	4,575 (2,075)
Max Load @ 25 lb/ft <sup>3</sup>	lbs (kg)	3,500 (1,588)	5,000 (2,268)
Floor Thickness	in (mm)	1/2 (13)	
Sidewall Thickness	in (mm)	1/4 (6)	
Door Opening Height x Width (Side - 2 Locations)	in (mm)	31 (787) x 24 (610)	
Screw Flighting Thickness	in (mm)	1/2 (13)	
Screw Height x Diameter	in (mm)	34 x 57 (864 x 1,448)	44 x 57 (1,118 x 1,448)
Knife Positions		4	5
Operating Speed	RPM	1000 or 1800	
Drive Package		1 or 2 Motor Belt & Pulley / 1 or 2 Motor Belt & Pulley w 2 Speed / 2 Speed (PTO)	
Minimum HP (Continuous Run)	HP	10 - 40, Drive Specific	
Scale System		3-Point	
<b>OPTIONS</b>			
Vertical Mixer Screw Knives Side Extensions	Discharge Magnet Tub Mounted Magnet	Scale Systems - Digi-Star®, - dinamica generale® - Weigh-Tronix®	Ladder



**CAUTION:** Never operate Patz equipment without all shields and guards in place. **Safety Is No Accident.** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.