


800 Series II Stationary Single Screw Vertical Mixer

Specifications



800 Series II  Tru Taper™	U/M	270	350
Mixing Capacity w/ Extensions (12 in)	ft ³ /m ³	335 (9.5)	425 (12)
Empty Weight	lbs (kg)	5,995 (2,719)	6,446 (2,924)
Max Load @ 25 lb/ft ³	lbs (kg)	6,750 (3,062)	8,750 (3,969)
Floor Thickness	in (mm)	1/2 (13)	
Sidewall Thickness	in (mm)	1/4 (6.4)	
Door Opening Height x Width (Side - 2 Locations)	in (mm)	39 (990) x 34 (864)	
Door Opening Height x Width (Back)	in (mm)	26 (660) x 34 (864)	30 (762) x 34 (864)
Screw Flighting Thickness	in (mm)	1/2 (13)	
Screw Height x Diameter	in (mm)	34 (864) x 86 (2,184)	44 (1118) x 86 (2,184)
Knife Positions		5	7
Operating Speed	RPM	1000	
Drive Package		2 Speed; Direct Electric Drive / Belt & Pulley / Two Motor & One Motor	
Minimum PTO HP (Continuous Run)	HP	20 - 50	
Scale System		3-Point	

OPTIONS

Vertical Mixer Screw
 - Cone Top
 - Knives
 Side Extensions
 - Metal

Discharge Chute w/ or w/o Magnet
 Discharge Conveyor
 Tub Mounted Magnet

Selection of Indicators
 - Digi-Star®,
 - Dinamica Generale®
 - Weigh-Tronix®

Ladder (Rear Location)
 Planetary Cooling System



CAUTION: Never operate Patz equipment without all shields and guards in place. **Safety Is No Accident.** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.