


1600 Series II Truck Mount Twin Screw Vertical Mixer Specifications



1600 Series II  Tru Taper®	U/M	620
Mixing Capacity w/ Extensions (9.25 in)	ft ³ /m ³	720 (20.3)
Empty Weight	lbs (kg)	11,700 (5,307)
Max Load @ 25 lb/ft ³	lbs (kg)	15,500 (7,031)
Mixer Width	in (m)	101 (2.6)
Floor Thickness	in (mm)	5/8 (16)
Sidewall Thickness	in (mm)	1/4 (6)
Door Opening Height x Width (Front - Back)	in (mm)	30 (762) x 34 (864)
Door Opening Height x Width (Side - 4 Locations)	in (mm)	39 (991) x 34 (864)
Viewing Platform		Front; Right/Left Access
Screw Flighting Thickness	in (mm)	5/8 (16)
Screw Height x Diameter	in (mm)	34 (864) x 86 (2,184.4) or 44 (1,117.6) x 86 (2,184.4)
Knife Positions Per Screw		7
Operating Speed	RPM	1,000
Drive Package		Planetary Drive
Scale System		4-Point

OPTIONS

Vertical Mixer Screw
 - Multi-Angle
 - Knives
 Side Extensions
 - Rubber

Hay Retainer
 Discharge Chute w/ or w/o Magnet
 Discharge Conveyor
 Tub Mounted Magnet

Selection of Indicators
 - Digi-Star®,
 - dinamica generale®
 - Weigh-Tronix®

Camera Package
 Ladder (Rear Location)
 Planetary Cooling System
 Hydraulic Control Center



CAUTION: Never operate Patz equipment without all shields and guards in place. **Safety Is No Accident.** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.