

2600 SERIES TRUCK MOUNT TWIN SCREW VERTICAL MIXERS



THE MOST TRUSTED MIXER THE MOST VALUED MIX

- ✓ **Consistent** TMR beyond demo and after the sale - precision feeding for service life.
- ✓ **Capacity** with Balanced Flow™ Technology - no dead spots at struck height!
- ✓ **Cleanout** minimizes residue carryover for balanced rations, batch integrity, and nutrient cost control.

FEEDINGSOLUTIONS
www.patzcorp.com


FEEDING IS BELIEVING!
Schedule a DEMO Today!

INVESTMENT FLEXIBILITY
Ask Dealer for Financing Details



2600 Series Truck Mount Twin Screw Vertical Mixer Specifications



2600 Series Vortex® 	U/M	975	1115 FT ³ Size Kit	1220 FT ³ Size Kit
Mixing Capacity w/ Extensions (9.25 in)	ft ³ /m ³	975 (27.6)	1,115 (31.6)	1,220 (34.5)
Empty Weight (Standard)	lbs (kg)	14,750 (6,690)	15,301 (6,940)	15,560 (7,058)
Empty Weight (XH)	lbs (kg)	17,100 (7,756)	17,651 (8,006)	17,910 (8,124)
Max Load @ 25 lb./ft. ³	lbs (kg)	24,375 (11,056)	27,875 (12,644)	30,500 (13,835)
Max Gross Weight (XH)	lbs (kg)	41,475 (18,813)	45,526 (20,650)	48,410 (21,958)
Floor Thickness	in (mm)	3/4 (19)		
Sidewall Thickness	in (mm)	1/4 (6); XH 3/8 (9)		
Door Opening Height x Width (Front - Back)	in (mm)	30 x 42 (762 x 1,067)		
Door Opening Height x Width (Side - 4 Locations)	in (mm)	39 x 34 (991 x 864)		
Screw Flighting Thickness	in (mm)	5/8 (16); XH 3/4 (19)		
Screw Height x Diameter	in (mm)	44 x 108 (1,118 x 2,743)		
Knife Positions Per Screw		7		
Operating Speed (Planetary)	RPM	1,000		
Drive Package		Low Profile Planetary		
Scale System		4-Point		
OPTIONS				
Vertical Mixer Screws Knives Side Extensions	Hay Retainer Discharge Chute w/ or w/o Magnet Discharge Conveyor Tub Mounted Magnet	Scale Systems - Digi-Star®, - dinamica generale® - Weigh-Tronix®	Camera Package Viewing Platform Creep Drive Package	



CAUTION: Never operate Patz equipment without all shields and guards in place. **Safety Is No Accident.** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.