

800 SERIES II STATIONARY SINGLE SCREW VERTICAL MIXERS



FEEDINGSOLUTIONS
www.patzcorp.com

FEEDING IS BELIEVING!
Schedule a DEMO Today!


INVESTMENT FLEXIBILITY
Ask Dealer for Financing Details



800 Series II Stationary Single Screw Vertical Mixer

Specifications



800 Series II  Tru Taper™	U/M	270	350
Mixing Capacity w/ Extensions (12 in)	ft ³ /m ³	335 (9.5)	425 (12)
Empty Weight	lbs (kg)	5,995 (2,719)	6,446 (2,924)
Max Load @ 25 lb/ft ³	lbs (kg)	6,750 (3,062)	8,750 (3,969)
Floor Thickness	in (mm)	1/2 (13)	
Sidewall Thickness	in (mm)	1/4 (6.4)	
Door Opening Height x Width (Side - 2 Locations)	in (mm)	39 (990) x 34 (864)	
Door Opening Height x Width (Back)	in (mm)	26 (660) x 34 (864)	30 (762) x 34 (864)
Screw Flighting Thickness	in (mm)	1/2 (13)	
Screw Height x Diameter	in (mm)	34 x 86 (864 x 2,184)	44 x 86 (1,118 x 2,184)
Knife Positions		5	7
Operating Speed	RPM	1000 or 1800	
Drive Package		1 or 2 Motor Belt & Pulley / 1 or 2 Motor Belt & Pulley w 2-Speed / 2 Speed (PTO) / Direct Electric Drive	
Minimum HP (Continuous Run)	HP	20 - 50, Drive Specific	
Scale System		3-Point	

OPTIONS

Vertical Mixer Screw
Knives
Side Extensions

Discharge Chute w/ or w/o Magnet
Tub Mounted Magnet

Scale Systems
- Digi-Star®,
- dinamica generale®
- Weigh-Tronix®

Ladder



CAUTION: Never operate Patz equipment without all shields and guards in place. **Safety Is No Accident.** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.