

1600 SERIES II TRUCK MOUNT TWIN SCREW VERTICAL MIXERS



THE MOST TRUSTED MIXER *THE MOST VALUED MIX*

- ✓ **Consistent** TMR beyond demo and after the sale - precision feeding for service life.
- ✓ **Capacity** with Balanced Flow™ Technology - no dead spots at struck height!
- ✓ **Cleanout** minimizes residue carryover for balanced rations, batch integrity, and nutrient cost control.

FEEDINGSOLUTIONS
www.patzcorp.com

FEEDING IS BELIEVING!
Schedule a DEMO Today!

INVESTMENT FLEXIBILITY
Ask Dealer for Financing Details



1600 Series II Truck Mount Twin Screw Vertical Mixer

Specifications



1600 Series II  Tru Taper®	U/M	620
Mixing Capacity w/ Extensions (9.25 in)	ft ³ /m ³	720 (20.3)
Empty Weight (no conveyor)	lbs (kg)	10,500 (4,773)
Max Load @ 25 lb/ft ³	lbs (kg)	15,500 (7,031)
Floor Thickness	in (mm)	5/8 (16)
Sidewall Thickness	in (mm)	1/4 (6)
Door Opening Height x Width (Front - Back)	in (mm)	30 x 34 (762 x 864)
Door Opening Height x Width (Side - 4 Locations)	in (mm)	39 x 34 (991 x 864)
Screw Flighting Thickness	in (mm)	5/8 (16)
Screw Height x Diameter	in (mm)	34 x 86 (864 x 2,184) / 44 x 86 (1,117 x 2,184)
Knife Positions Per Screw		7
Operating Speed	RPM	1,000
Drive Package		Planetary Drive
Scale System		4-Point
OPTIONS Vertical Mixer Screw Knives Side Extensions Hay Retainer Discharge Chute w/ or w/o Magnet Discharge Conveyor Tub Mounted Magnet Scale Systems - Digi-Star®, - dinamica generale® - Weigh-Tronix® Camera Package Viewing Platform Creep Drive Package		



CAUTION: Never operate Patz equipment without all shields and guards in place. **Safety Is No Accident.** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.