2600 SERIES TRUCK MOUNT TWIN SCREW VERTICAL MIXERS



THE MOST TRUSTED MIXER

THE MOST VALUED MIX

- Consistent TMR beyond demo and after the sale precision feeding for service life.
- (✓) Capacity with Balanced Flow™ Technology no dead spots at struck height!
- (V) Cleanout minimizes residue carryover for balanced rations, batch integrity, and nutrient cost control.





2600 Series Truck Mount Twin Screw Vertical Mixer **Specifications**



U/M	975	1115 FT³ Size Kit	1220 FT³ Size Kit
ft³/m³	975 (27.6)	1,115 (31.6)	1,220 (34.5)
Ibs (kg)	14,750 (6,690)	15,301 (6,940)	15,560 (7,058)
lbs (kg)	17,100 (7,756)	17,651 (8,006)	17,910 (8,124)
lbs (kg)	24,375 (11,056)	27,875 (12,644)	30,500 (13,835)
lbs (kg)	41,475 (18,813)	45,526 (20,650)	48,410 (21,958)
in (mm)	3/4 (19)		
in (mm)	1/4 (6); XH 3/8 (9)		
in (mm)	30 x 42 (762 x 1,067)		
in (mm)	39 x 34 (991 x 864)		
in (mm)	5/8 (16); XH 3/4 (19)		
in (mm)	44 x 108 (1,118 x 2,743)		
	7		
RPM	1,000		
	Low Profile Planetary		
	4-Point		
	ft³/m³ Ibs (kg) Ibs (kg) Ibs (kg) Ibs (kg) in (mm) in (mm) in (mm) in (mm)	ft³/m³ 975 (27.6) lbs (kg) 14,750 (6,690) lbs (kg) 17,100 (7,756) lbs (kg) 24,375 (11,056) lbs (kg) 41,475 (18,813) in (mm) in (mm) in (mm) in (mm) RPM	ft³/m³ 975 (27.6) 1,115 (31.6) lbs (kg) 14,750 (6,690) 15,301 (6,940) lbs (kg) 17,100 (7,756) 17,651 (8,006) lbs (kg) 24,375 (11,056) 27,875 (12,644) lbs (kg) 41,475 (18,813) 45,526 (20,650) in (mm) 3/4 (19) in (mm) 1/4 (6); XH 3/8 (9) in (mm) 39 x 34 (991 x 864) in (mm) 5/8 (16); XH 3/4 (19) in (mm) 44 x 108 (1,118 x 2,743) 7 RPM 1,000 Low Profile Planetary

OPTIONS

Vertical Mixer Screws Knives Side Extensions

Hay Retainer Discharge Chute w/ or w/o Magnet Discharge Conveyor Tub Mounted Magnet

Scale Systems - Digi-Star®, dinamica generale® - Weigh-Tronix®

Camera Package Viewing Platform Creep Drive Package



CAUTION: Never operate Patz equipment without all shields and guards in place. Safety Is No Accident. Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.





