

3800 SERIES II TRAILER TRIPLE SCREW VERTICAL MIXERS



HIGH CAPACITY MIXING *FOR HIGH VOLUME FEEDING*

NEW TMR Vertical Mixer with *Size Kit Options*
for Added Mixing Capacity!



THE MOST TRUSTED MIXER *THE MOST VALUED MIX*

- ✓ **Consistent** TMR beyond demo and after the sale - precision feeding for service life.
- ✓ **Capacity** with Balanced Flow Technology™ - no dead spots at struck height!
- ✓ **Cleanout** minimizes residue carryover for balanced rations, batch integrity, and nutrient cost control.

FEEDING IS BELIEVING!
Schedule a DEMO Today!


FEEDINGSOLUTIONS
www.patzcorp.com

INVESTMENT FLEXIBILITY
Ask Dealer for Financing Details



3800 Series II Trailer Triple Screw Vertical Mixer

Specifications



3800 Series II  Vortex®		U/M	1450XH	1675 FT³ Size Kit	1825 FT³ Size Kit
Mixing Capacity	ft³ (m³)		1450 (41.1)	1,675 (47.4)	1,825 (51.7)
XH Empty Weight	lbs (kg)		37,900 (17,191)	38,650 (17,532)	38,975 (17,652)
Max Load @ 25 lb/ft³	lbs (kg)		36,250 (16,443)	41,875 (18,994)	45,625 (20,695)
XH Max Gross Weight	lbs (kg)		74,150 (33,634)	80,525 (36,526)	84,600 (35,374)
Overall Height	in (m)		121.4 (3.1)	129.8 (3.3)	136.5 (3.5)
Floor Thickness	in (mm)		3/4 (19)		
Sidewall Thickness	in (mm)		XH 3/8 (9)		
Door Opening Height x Width (Front/Back)	in (mm)		30 (762) x 47 (1,194)		
Door Opening Height x Width (Side - 2 Locations)	in (mm)		39 (991) x 34 (864)		
Viewing Platform			Front w/ Left Access		
Screw Flighting Thickness	in (mm)		STD 5/8 (16) / XH 3/4 (19)		
Screw Height x Diameter	in (mm)		44 (1,117.6) x 108 (2,743)		
Knife Positions Per Screw			7		
Operating Speed	RPM		700 - 1,000		
Drive Package			2-Speed Stop and Shift / T3™ Autoshift		
Minimum PTO HP (Continuous Run)	HP		250		
Trailer Type			Split Dual; Tandem Walking Beam		
Scale System			4-Point		
Tires			(8) 315/80R22.5 Dual Tires		

OPTIONS				
Vertical Mixer Knives - Serrated - Raptor®	Side Extensions - Rubber/Steel for 1450 Size Kits - 1,675 ft³ & 1,825 ft³ for Added Mixing Capacity	Discharge Chute w/ or w/o Magnet Discharge Conveyor Tub Mounted Magnet	Selection of Indicators - Digi-Star® - dinamica generale® - Weigh-Tronix®	Camera Package Hydraulic Control Center



CAUTION: Never operate Patz equipment without all shields and guards in place. **Safety Is No Accident.** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.



Patz Corporation • Pound, Wisconsin USA
Ph: (920) 897-2251 • info@patzcorp.com • www.patzcorp.com



PA-34060 10/24 ©2024 Patz Corporation Printed in U.S.A.