600 SERIES STATIONARY SINGLE SCREW
VERTICAL MIXERS

FEEDINGSOLUTIONS
www.patzcorp.com

FEEDING IS BELIEVING!
Schedule a DEMO Today!

INVESTMENT FLEXIBILITY
Ask Dealer for Financing Details

600 Series Stationary Single Screw Vertical Mixer
Specifications

600 Series Tru Taper™	U/M	185
Mixing Capacity w/ Extensions (12 in)	ft^3/m^3	235 (6.6)
Empty Weight	lbs (kg)	5,517 (2,503)
Max Load @ 25 lb/ft^3	lbs (kg)	4,625 (2,102)
Floor Thickness	in (mm)	1/2 (13)
Sidewall Thickness	in (mm)	1/4 (6)
Door Opening Height x Width (Side - 2 Locations)	in (mm)	31 (787) x 24 (610)
Screw Flighting Thickness	in (mm)	1/2 (13)
Screw Height x Diameter	in (mm)	34 x 66 (864 x 1,676) or 44 x 66 (1,118 x 1,676)
Knife Positions		4 (34 in) or 5 (44 in)
Operating Speed	RPM	1000 or 1800
Drive Package		1 or 2 Motor Belt & Pulley / 1 or 2 Motor Belt & Pulley w 2-Speed / 2-Speed (PTO)
Minimum HP (Continuous Run)	HP	10-40, Drive Specific
Scale System		3-Point

OPTIONS

Vertical Mixer Screw
Knives
Side Extensions

Discharge Magnet
Tub Mounted Magnet

Scale Systems
- Digi-Star®,
- dinamica generale®
- Weigh-Tronix®

Ladder

SAFETY! It's no accident

CAUTION: Never operate Patz equipment without all shields and guards in place. ***Safety Is No Accident.*** Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times. Additionally, make sure all safety shields and devices are functioning properly and are securely in place. Specifications and prices subject to change without notice.

PA-28442 2/24 ©2024 Patz Corporation Printed in U.S.A

Patz Corporation Pound, WI USA Ph: (920) 897-2251 www.patzcorp.com info@patzcorp.com